

Paraffin wax 1-3

> Product Description

Paraffin wax (or petroleum wax) is a soft colorless solid derived from petroleum, coal, or oil shale that consists of a mixture of saturated hydrocarbon molecules containing between 20 and 40 carbon atoms.

> Application

Candle, T-light, Crayon, Textile, Battery, Precision Casting, Knitting, Metal plating, Telecommunication and leather industry,

> Characteristics

No	CHARACTERISTIC	ACCEPTED LIMIT	
1	Appearance	Colorless or white or almost white mass; the melted	
	BP 2022	substance is free from fluorescence in daylight	
2	Solubility	Practically insoluble in water, freely soluble in	
	BP 2022	methylene chloride, practically insoluble in ethanol	
		(96 percent)	
3	Oil content %	1-3	
	ASTM D-721		
4	Odor	Odorless	-
5	Kinematic Viscosity @100 °C	6-8	cSt
	ASTM D-445		
6	Color Lovibond	0.1-0.2	Y
	IP 17 cell 2"		
7	Drop Melting Point	65-75	°C
	ASTM D-127		
8	Congealing point	65-75	°C
	ASTM D-938		
9	Flash Point	Min 180	°C
	ASTM D-92		
10	Needle Peneteration		-
	ASTM D-1321		
11	Acidity or Alkalinity	Not more than 0.5 mL of 0.01 M hydrochloric acidis	
	BP 2022	required to change the color of the indicator to red.	
12	Polycyclic Aromatic Hydrocarbons	Absorbance of test solution remains $< 1/3$ rd that of	
	BP 2022	reference solution at 275 nm, throughout 260 – 420	
		nm wavelengths	
13	Sulphates	Maximum 150	ppm
	BP 2022		

> Packing

25 KG carton box and/or PE laminated bag

> Storage

Protect from light

Heat- sensitive

Paraffin will be shipped in bags or boxes and has to be stowed in a cool sun-protected place.